

Resichem 508 UVPU

solvent based polyurethane top coat, UV Stable

is a two component solvent based low viscosity polyurethane top coat for primed metallic and concrete surfaces. Resichem 508 UVPU is proven to offer long term asset protection with excellent UV stability.

- Solvent based polyurethane technology
- Two component
- Apply by brush, roller or standard airless spray
- Excellent flexibility once cured
- Apply to metallic surfaces primed with 506 Aluprime or 501 CRSG
- Apply to concrete surfaces primed with 503 SPEP and 505 Damp Seal
- UV stable
- Provides long term protection in C1-C5 corrosive environments
- Available in a wide range of RAL or BS colours



Training facility in the UK was refurbished using Resimac corrosion protection systems. All surfaces were mechanically abraded and primed with 506 Aluprime and top coated with 508 UVPU



Concrete surfaces of a subway were mechanically abraded, primed with 503 SPEP and top coated with 508 UVPU





The external tank surfaces were mechanically abraded and primed using Resichem 501 CRSG, once cured a single coat of 508 UVPU was applied to give a UV stable finish to the tank surface

This material can be used to resurface and protect—

- **Bridges**
- **Stairways**
- **External tank surfaces**
- **Structural steel**
- **Machinery**
- **External pipe surfaces**
- **Transformers**
- **Steel containers**
- **Pump & Valve casings**



Grain silo required a 15 year + coating system to protect from further surface corrosion. The mechanically prepared surface was primed with 2 x coats of 506 Aluprime and top coated with 2 x coats of 508 UVPU

